




Glacier Oak

- ◊ Synchronized pore optics (EIR)
- ◊ Integrated underlay mat (-20 dB)
- ◊ Endless decor variation
- ◊ Large areas can be laid (up to 400 m²)
- ◊ Dimensionally stable & water resistant
- ◊ Only 4,8 mm construction height
- ◊ Format: 1220 x 230 mm
- ◊ Wear layer: 0,3 mm
- ◊ Carton content: 8 planks = 2,245 m²
- ◊ Suitable for hot water and electric underfloor heating
- ◊ Patented Uniclic connection
- ◊ Low emissions (Certified A+)
- ◊ Utilization class 23/31
- ◊ Free from phthalates and plasticizers

Note before laying:

- Amount needed + 10% of the area.
- Subfloor clean, hard, flat, stable and firm.
- Uneven surface = max 3 mm per 1,2 m.
- Acclimatize the planks horizontally in the room for at least 48h!
- **Important:** Room temperature = floor temperature during installation
- Use temperature 13°C to 32°C.

Note during laying:

- Linoleum and wood-based subfloors require decoupling with 0,2 mm PE foil!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 6-8 mm.
- Max 20 x 20 m (400 m²) without expension joints.
- Do **not** use an additional underlay mat.



The pictures may differ in color from the original product.

Article No.	Decor No.	Description	EAN	Pack/Pallet
106203757	M86264L-018B	Strong SPC Variant, Glacier Oak	7640165929339	36