



Yosemite Oak

- ◇ Synchronized pore optics (EIR)
- ◇ Integrated underlay mat (-20 dB)
- ◇ Endless decor variation
- ◇ Large areas can be laid (up to 400 m²)
- ◇ Dimensionally stable & water resistant
- ◇ Only 4,8 mm construction height
- ◇ Format: 1220 x 230 mm
- ◇ Wear layer: 0,3 mm
- ◇ Carton content: 8 planks = 2,245 m²
- ◇ Suitable for hot water and electric underfloor heating
- ◇ Patented Uniclic connection
- ◇ Low emissions (Certified A+)
- ◇ Utilization class 23/31
- ◇ Free from phthalates and plasticizers

Note before laying:

- Amount needed + 10% of the area.
- Subfloor clean, hard, flat, stable and firm.
- Uneven surface = max 3 mm per 1,2 m.
- Acclimatize the planks horizontally in the room for at least 48h!
- **Important:** Room temperature = floor temperature during installation
- Use temperature 13°C to 32°C.

Note during laying:

- Linoleum and wood-based subfloors require decoupling with 0,2 mm PE foil!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 6-8 mm.
- Max 20 x 20 m (400 m²) without expension joints.
- Do **not** use an additional underlay mat.



The pictures may differ in color from the original product.

Article No.	Decor No.	Description	EAN	Pack/Pallet
106203755	M81243L-6	Strong SPC Variant, Yosemite Oak	7640165929315	36