




CROSS-SECTION

- 1. Transparent wear layer
- 2. High resolution décor film
- 3. Vinyl backing
- 4. SPC Core (Stone Polymer Composite)
- 5. Click System
- 6. Vinyl backing
- 7. Integrated noise-absorbing underlayment



GERDOO


- ◊ Natural wood look
- ◊ Can be laid on large areas (400 m²)
- ◊ Water resistant
- ◊ Only 6,5 mm mounting height
- ◊ Vinyl- and wear layer 1,2/0,55 mm
- ◊ Format 935 x 465 mm – Large size!
- ◊ Carton content = 4 planks = 1,739 m²
- ◊ Suitable for electric underfloor heating
- ◊ Patented click connection
- ◊ Low Emission (Certified A +)
- ◊ Integrated underlay mat
- ◊ Step & room sound reduction (18 dB)
- ◊ Utilization class 23 / 32
- ◊ Phthalate and plasticizer free

Note before laying:

- Amount needed + 10% of the area.
- Subfloor clean, hard, flat, stable and firm.
- Uneven surface = max 3 mm per 1,2 m.
- Acclimatize the planks horizontally in the room for at least 48h!
- **Important:** Room temperature = floor temperature during installation
- Use temperature 18°C to 24°C.

Note during laying:

- Linoleum and wood-based subfloors require decoupling with 0,2 mm PE foil!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 6-8 mm.
- Max 20 x 20 m (400 m²) without expansion joints.
- Do not use an additional underlay mat.



The pictures may differ in color from the original product.

Article No.	Decor No.	Description	EAN	Pack/Pallet
106203610	MJ8002-2	Strong SPC Multilayer Plus, Gerdoo	7640165925300	34