



The pictures may differ in color from the original product.

## Columbia Eiche

- ◇ Synchronized pore wood look
- ◇ Dimensionally stable, up to 400 m<sup>2</sup> continuously laid without expansion joints
- ◇ Water resistant and phthalates free
- ◇ Only 4,8 mm mounting height
- ◇ Wear layer 0,5 mm
- ◇ L 1220 x W 228 mm
- ◇ Carton content = 8 planks = 2,23 m<sup>2</sup>
- ◇ Simple, floating installation
- ◇ I4F Drop Down connection
- ◇ Low Emission (Certified A +)
- ◇ Suitable for hot water and electric floor heating systems
- ◇ Utilization class 23/34

### Note before laying:

- Amount needed + 10% of the area
- Subfloor clean, hard, flat, stable and firm
- Uneven surface = max 3 mm per 1,2 m
- **Important:** Room temperature = floor temperature = use temperature 15°C to 60°C

### Note during laying:

- If underlay mat is required: use a flameproof and vinyl approved mat (at least 500 kPa, 1,5 mm thickness and non-sticky underlay mat)
- On linoleum and wood-based subfloors is an underlay mat or 0,2 mm PE building foil for decoupling absolutely necessary!
- The planks must be properly clicked in!
- Use spacers between walls and fixed objects of 8-10 mm
- Maximum field size 20 x 20 m



Article No.	Facido No.	Description	EAN	Pack/Pallet
27706741	106100230	b!design SPC, Columbia Eiche, 4,8 mm	7640165927519	33