



VIRGINIA OAK


- ◇ Embossed in register (EIR)
- ◇ Dimensionally stable
- ◇ Endless decor variation
- ◇ Can be laid on large areas (400 m²)
- ◇ Water resistant
- ◇ Only 3,8 mm mounting height
- ◇ Format 1220 x 228 mm
- ◇ Wear layer 0,5 mm
- ◇ Carton content 10 planks = 2,782 m²
- ◇ Suitable for electric underfloor heating
- ◇ Patented I4F click connection
- ◇ Low Emission (Certified A +)
- ◇ Utilization class 23/33
- ◇ Phthalate and plasticizer free

Note before laying:

- Amount needed + 10% of the area
- Subfloor clean, hard, flat, stable and firm
- Uneven surface = max 3 mm per 1,2 m
- Acclimatize the planks horizontally in the room for at least 24h!
- **Important:** Room temperature = floor temperature during installation
- Use temperature 15°C to 60°C
- The underlay mat need to have a pressure resistance of at least 500 kPa, maximum 1,5 mm thickness and maximum 0,5 mm unevenness.
Recommendation: dB Cover LVT/SPC 1.5

Note during laying:

- Linoleum and wood-based subfloors require decoupling with 0,2 mm PE foil!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of > 8 mm
- Max 20 x 20 m (400 m²) without expansion joints



The pictures may differ in color from the original product.

Article No.	Decor No.	Description	EAN	Pack/Pallet
106203708	ST190EL-22	Strong SPC Structure: Virginia Oak	7640165927588	33