



Winkelprofil Nr. 162, 24,5 x 20 mm

- Aluminium.
- Ungelocht.
- Auf Anfrage biegsam.

Werkstoff:	EN AW 6063 (DIN EN 573)
Werkstoffzustand:	T6 (DIN EN 755-2)
Vorbehandlung:	E6 (DIN EN 17 611)
Schichtdicke Eloxal:	Klasse 15 (DIN EN 17 611)

Zubehör:	Befestigungsmaterial.
Geeignet für:	Designbelag / LVT Click und Loose Lay, Designbelag / LVT Dryback, Textile und elastische Bodenbeläge, Laminat / Multilayer
Montageart:	Kleben, Schrauben
Längen:	500 cm, 250 cm
Farbe:	silber

Winkelprofile sind ideal geeignet als kleiner Treppenwinkel, als Türschwellenprofil oder als Abschluss an Podesten.
Sie schützen die Kanten des Bodenbelags dauerhaft.



Angle edge no. 162, 24.5 x 20 mm

- Aluminium.
- Without screw holes.
- Bendable on request.

Material:	EN AW 6063 (DIN EN 573)
Material condition:	T6 (DIN EN 755-2)
Pre-treatment:	E6 (DIN EN 17 611)
Thickness of anodised layer:	Class 15 (DIN EN 17 611)

Accessories:	Fastening material.
Suitable for:	Design flooring / LVT click and loose lay, Design flooring / LVT dryback, Textile and elastic floor coverings, Laminate / multilayer
Installation:	gluing, screwing
Lengths:	500 cm, 250 cm
Colour:	silver

Angle edges are ideally suited as a small staircase angle, as a door threshold profile or as a termination on platforms.
They protect the edges of the flooring permanently.